

### **Listing of Claims:**

This listing of claims reflects all claim amendments and replaces all prior versions, and listings, of claims in the application. Material to be inserted is in **bold and underline**, and material to be deleted is in ~~strikeout~~ or (if the deletion is of five or fewer consecutive characters or would be difficult to see) in double brackets [[ ]]. In brief, claims 1, 4, 6, 9, 12, 13, 15, 16, 18, 23, 26, 28, and 43 have been amended, claims 2 and 44-55 have been canceled, without prejudice, and new claims 56 and 57 have been added.

1. (Currently Amended) A guide device for guiding ~~at least one of~~ a hole-forming tool and/or a fastener to a **bone plate** ~~bone repair device~~, comprising:

a coupling portion configured to be connected to the **bone plate** ~~bone repair device~~ adjacent ~~a first surface of~~ a bone; and

a guide portion connected to the coupling portion **such that the guide portion is disposed across the bone from the coupling portion**, [[and]] **the guide portion being** configured to guide the ~~at least one~~ hole-forming tool and/or fastener into the bone and then to a predefined position of the **bone plate** ~~bone repair device~~,

~~wherein the guide portion is configured to be disposed adjacent a second surface of the bone that generally opposes the first surface on the bone.~~

2. (Canceled)

3. (Canceled)

4. (Currently Amended) The guide device of claim 1, wherein the **bone plate** ~~bone repair device~~ includes an inner surface that faces the bone and an outer surface

that opposes the inner surface, and wherein the guide portion is disposed closer to the inner surface than the outer surface.

5. (Original) The guide device of claim 1, wherein the predefined position is a threaded opening.

6. (Currently Amended) The guide device of claim 5, the threaded opening being a plurality of threaded openings included in the **bone plate** ~~bone repair device~~, wherein the guide portion is configured to guide fasteners through the bone and then to each of the threaded openings.

7. (Original) The guide device of claim 1, wherein the guide portion includes a frame and a guide element coupled movably to the frame, and wherein the guide element defines a guide axis intersecting the predefined position.

8. (Original) The guide device of claim 7, wherein the guide element is movable parallel to the guide axis.

9. (Currently Amended) The guide device of claim 8, wherein the guide element includes indicia configured to measure a distance along the guide axis, and wherein the distance corresponds to a spacing of the **bone plate** ~~bone repair device~~ from the guide element.

10. (Original) The guide device of claim 8, wherein the guide portion includes a detent mechanism configured to restrict movement of the guide element.

11. (Original) The guide device of claim 10, wherein the detent mechanism is configured to permit movement of the guide element toward the bone and to restrict movement of the guide element away from the bone.

12. (Currently Amended) The guide device of claim 7, wherein the **bone plate** ~~bone repair device~~ includes a plurality of predefined positions, and wherein the guide element is movable to define spaced guide axes intersecting each of the predefined positions.

13. (Currently Amended) The guide device of claim 1, wherein the guide portion is configured to be movable into engagement with the bone so that the bone is pushed toward the **bone plate** ~~bone repair device~~.

14. (Original) The guide device of claim 1, further comprising a spacer portion connecting the coupling portion to the guide portion, the spacer portion being disposed external to the bone.

15. (Currently Amended) A guide device for guiding ~~at least one of~~ a hole-forming tool and/or a fastener to a connective feature of a **bone plate** ~~bone repair device~~, comprising:

a coupling portion configured to be connected to the **bone plate** ~~bone repair device~~ adjacent a bone; and

a guide portion connected to the coupling portion and configured to be disposed **across the bone from the coupling portion** in a predefined relation to the **bone plate**, ~~bone repair device so~~ **such** that the guide portion defines a guide axis extending from the guide portion, through the bone, and then to the connective feature of the **bone plate** ~~bone repair device~~.

16. (Currently Amended) The guide device of claim 15, the connective feature being a plurality of connective features included in the **bone plate** ~~bone repair device~~,

wherein the guide portion is configured to define a plurality of guide axes that intersect respective connective features.

17. (Original) The guide device of claim 16, wherein the guide portion includes a frame and a guide element movable within the frame to define the plurality of guide axes.

18. (Currently Amended) The guide device of claim 15, wherein the guide portion includes a guide element defining the guide axis, and wherein the guide element is configured to be movable parallel to the guide axis while the coupling portion is connected to the bone plate.

19. (Original) The guide device of claim 18, wherein the guide portion includes a detent mechanism configured to restrict movement of the guide element.

20. (Original) The guide device of claim 19, wherein the detent mechanism is configured to permit movement of the guide element toward the bone and to restrict movement of the guide element away from the bone.

21. (Original) The guide device of claim 19, wherein the detent mechanism is configured to be releasable manually without tools.

22. (Original) The guide device of claim 15, wherein the guide portion includes a removable cannula defining the guide axis.

23. (Currently Amended) The guide device of claim 15, wherein the bone is a ~~distal~~ radius bone, and wherein the bone-repair device is a bone plate configured to be connected adjacent a distal volar surface of the ~~distal~~ radius bone.

24. (Original) The guide device of claim 15, further comprising a spacer portion configured to connect the coupling and guide portions external to the bone.

25. (Original) The guide device of claim 15, wherein the guide portion includes indicia configured to measure a distance along the guide axis.

26. (Currently Amended) The guide device of claim 25, wherein the distance corresponds to a spacing of the **bone plate** ~~bone repair device~~ from the guide portion.

27. (Original) The guide device of claim 15, wherein the connective feature is a threaded opening.

28. (Currently Amended) A system for fixing a bone, comprising:  
a bone plate including a connective feature; and  
a guide device configured to guide ~~at least one of~~ a hole-forming tool and/or a fastener through the bone and then to the connective feature, including (1) a coupling portion configured to be connected to the bone plate, and (2) a guide portion connected to the coupling portion and configured to be disposed **across the bone from the coupling portion** in a predefined relation to the bone plate so that the guide portion defines at least one guide axis **for intersecting** the connective feature of the bone plate.

29. (Original) The system of claim 28, wherein the bone plate defines an array of threaded openings, and wherein the at least one guide axis is a plurality of guide axes intersecting each of the threaded openings.

30. (Original) The system of claim 28, wherein the bone plate defines at least one additional connective feature configured to position the coupling portion in relation to the bone plate.

31. (Original) The system of claim 28, wherein the bone plate and the guide device are configured in correspondence for use on one of a left and a right side of a body.

32-42. (Canceled)

43. (Currently Amended) A system for fixing ~~repairing~~ a bone with a bone plate, comprising:

means for coupling to the bone plate;

means for defining, at least substantially external to the bone, a guide axis that extends through the bone; and

means for directing a bone screw along the guide axis from a position across the bone from the means for coupling, through the bone, and into ~~then into threaded engagement with~~ an opening of the bone plate.

44-55. (Canceled)

56. (New) A guide device for guiding a hole-forming tool and/or a fastener to a bone plate secured to a bone, comprising:

a coupling portion that attaches to the bone plate;

a guide portion that defines a guide axis for a connective feature of the bone plate when the coupling portion is attached to the bone plate; and

an extension portion that connects the coupling portion to the guide portion, the extension portion extending around the bone, when the bone plate is secured to the bone, such that the guide portion and the coupling portion oppose one another across the bone.

57. (New) A system for bone fixation, comprising:

a bone plate structured to be secured to a bone and including a connective feature; and

a guide device including a guide portion and being structured to attach to the bone plate and to extend around the bone from the bone plate such that the guide portion opposes the bone plate across the bone and defines a guide axis for the connective feature of the bone plate.